



SCAN2K Laser Scanner

Compact, Powerful
Scanning Technology
from Teledyne Optech

The **SCAN2K Terrestrial Laser Scanner (TLS)** delivers accurate, precise data faster than ever before, bridging the gap between small, light-weight, short-range sensors and large, long-range, pulsed time-of-flight scanners. Built with surveyors in mind, the Scan2k has a user-friendly on-board operator interface with menu-driven operations for quickly collecting and georeferencing point cloud data.

With a powerful quad-core processor, an integrated high-resolution camera, a digital compass and inclinometer, an L1 GNSS receiver and weather-proof housing, the Scan2K can be deployed in various environments for a wide range of applications, using different workflows and setups. The Scan2K leads the market in price versus performance, starting at a price that rivals short-range scanners while outperforming long-range scanners. With accelerated performance and all the built-in features surveyors need, the Scan2K offers more flexibility than ever before. Whether on a tripod, vehicle, or moving platform, the outstanding performance of the Scan2K makes it the most versatile and efficient terrestrial laser scanner on the market.

www.carlsonsw.com



APPLICATIONS

- » Civil Engineering
- » Construction
- » Transportation
- » Mining
- » Architecture
- » Archaeology & Cultural Heritage
- » City Modeling
- » Geology
- » Industrial & Marine
- » Forensics
- » Forestry
- » Entertainment – Virtual Reality
- » And many more...



SENSOR FEATURES

- » Long-range capability
- » High-speed data acquisition
- » 100% scanning efficiency
- » Wide, selectable field of view
- » Multiple lidar returns
- » Internal cameras
- » External camera option

HARDWARE FEATURES

- » Weather-proof housing
- » Internal data storage
- » Internal hot-swappable batteries
- » Flexible external powering options
- » Tilt compensation
- » L1 GNSS receiver
- » Digital compass
- » Large, bright, on-board touchscreen
- » Laser plummet?

SOFTWARE FEATURES

- » Remote operation capability
- » Project planning
- » Direct georeferencing in the field
- » Automatic target recognition
- » Automatic target-free registration
- » Easy upgrades
- » Powerful bundled ATLAScan software

Specifications

Laser

Range measurement principle	Pulsed
Wavelength	1550 nm (invisible)
Laser safety classification	1 ²
Sample collection rate	Up to 2 MHz
Intensity recording	12 bits
Minimum range	1.5 m
Waveform digitizing technology (WFD)	Yes
Number of returns recorded	Up to 4 (first 2 and last 2)

Scanning Resolution

Angular measurement resolution	up to 12 µrad
Max. sample density [point to point spacing]	2 mm @ 100 m

Accuracy and Repeatability

Range accuracy (1 sigma)	5 mm @ 100 m
Range resolution	2 mm ⁸
Precision, single shot (1 sigma)	4 mm @ 100 m
Angular accuracy	80 µrad

Scanning Characteristics

Max. field of view (vertical)	120° (-45 to +70°)
Max. field of view (horizontal)	360°
Min. angular step size (vertical)	12 µrad
Min. angular step size (horizontal)	20 µrad

Additional sensors and features

Dual-axis inclinometer (accuracy)	Up to 0.01°
GNSS receiver	L1 GPS + GLONASS
External GNSS support	Yes, incl. antenna mount
Compass	Digital
Registration/orientation method	GNSS and compass, backsighting, resection
On-board registration data	Yes ⁴
On-board target acquisition RetrolD	Yes
Pause while scanning	Yes
Multiple scan area selection	Yes, multiple ROIs ⁵
On-board planning mode	Yes
Mobile operation	Yes

System Peripherals

Data storage capacity	250 GB internal SSD
-----------------------	---------------------

Communications / Data transfer

Wireless LAN	Yes
USB connector	Yes
Ethernet port	Yes
Communications/data transfer	100Mbit Ethernet, WLAN, USB



All specifications are subject to change without notice.

Imaging system

Internal cameras	Yes
Internal camera resolution	80-Mpix panoramic image
Export format of internal camera	JPEG
External camera DSLR	Yes with auto trigger
White-balancing DSLR	Yes
Export format of ext. camera	JPEG, NEF

Power

Power supply input voltage	9 to 32-V DC
Battery type	Internal, hot swappable Li-Ion batteries
Battery power	2.5 hours
Power consumption	60 W

Operation Characteristics

Operating temperature (min.) ⁹	-20°C (-4°F)
Operating temperature (max.)	+50°C (122°F)
Protection Class	IP64
Storage temperature	-40°C to +80°C (-40°F to +176°F)

Physical Characteristics

Height	323 mm (12.7")
Width	217 mm (8.5")
Total weight	11.2 kg (24.6 lbs.)

Control Options

On-board display	Touchscreen control, sunlight visible, 640x480, color
External user interfaces	Tablet, PC

ATLAScan software

Remote scanner control	Yes
Geo-referencing	Automatic
Target-free automatic alignment	Yes ⁵
Feature / primitive extraction	Yes
Terrain mesh	Yes
3D meshing	Yes
Measurements and calculations	Yes
Monitoring	Yes
Automatic line features extraction	Yes ⁶
Vegetation removal	Yes

² Max range tested on flat targets, larger than the laser beam diameter, perpendicular angle of incidence and STD Clear visibility (23 km)

³ Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007

⁴ Definition of multiple ROIs in a single scan is possible using ATLAScan Control module

⁵ Using the on-board georeferencing functionality

⁶ Successful pre-registration depends on the object geometry, scanning resolution and overlap (min. 20%) between different scanning positions

⁷ Automatic line extraction for break lines of a mesh (e.g. crests and toes of a terrain mesh)

⁸ Laser plummet is built into the Inbrach

⁹ Minimum distance that the Scan2K is able to separate two range measurements on objects in a similar bearing

¹⁰ Normal operation to -10°C, extended cold temperature operation to -20°C with Optech Cold Weather package.

Ordering information

Contact your local CARLSON LMD representative www.carlson.com